

WASTE BIN CONTAINERS

and Paper Only




CONTINENTAL T100



Black rubber wheels with polypropylene centre

Wheel description on page 58-60



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Dust seal: orange polyethylene
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake, total rear foot brake, centralised brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN
160	40	2.10	524410	2.38	525210	2.60	524010	199	140x110	105x80	11	56	156	150
200	50	2.72	524406	3.00	525206	3.22	524006	240	140x110	105x80	11	56	156	225



mm	mm	kg	CODE	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN
200	50	3.45	524206	240	140x110	105x80	11	56	40	34	16.5	225	

Options available to order



Directional lock for brackets d. 150-200 mm




Wheel with roller bearings



Wheel with grey rubber tyre

Black rubber wheels with pressed steel discs

Wheel description on page 66-68



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Dust seal: orange polyethylene
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake, total rear foot brake, centralised brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN
160	40	2.44	535010	2.69	535410	2.97	534010	199	140x110	105x80	11	56	156	180
200	50	3.25	535006	3.39	535406	3.67	534006	240	140x110	105x80	11	56	156	230



mm	mm	kg	CODE	mm	mm	mm	mm	mm	mm	mm	mm	daN
200	50	3.45	534806	240	140x110	105x80	11	56	40	34	16.5	230

Options available to order



Directional lock for brackets d. 150-200 mm




Wheel with roller bearings



Wheel with grey rubber tyre

Sigma Elastic rubber wheels with aluminium centre

Wheel description on page 224-226



- 1) Plate: galvanised colonial steel plate
 - 2) Fork: galvanised colonial steel plate
 - 3) Ball race ring: galvanised colonial steel plate
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: steel bolt in grade 8.8 steel and steel nut
- Available with adjustable total rear foot brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN
200	50	4.46	727516	3.00	728516	5.06	727206	250	140x110	105x80	11	56	126	500

TEST REPORT ACCORDING TO UNI EN 840-5: 2013

The TR Lab, Test & Research laboratory of Tellure Rôta has the necessary equipment for Dynamic testing on wheel and castor according to **UNI EN 840-5:2013, par. 4.9.3.** The laboratory issues a test report with the results of the tests.

